

# Triflex UltraCleaner



## Use

Triflex UltraCleaner serves as a universal cleaning and degreasing agent for the treatment of coated and uncoated surfaces. Triflex UltraCleaner is a powerful, water-soluble and safe cleaner. The cleaner is biodegradable and allows for quick and efficient removal of dirt.

Among other things, the following contaminants can be removed: Grease, dirt, carbon, oil, soot, nicotine deposits and other stubborn stains.

## Components

Component	Product
Cleaner	Triflex UltraCleaner

## Packaging

Component	Pack size
Cleaner	Spray bottle: 0.50L
Cleaner	Canister: 10L

## Application method

### Spray bottle:

Apply Triflex UltraCleaner using the spray bottle to the soiled surface, let it soak into the surface for a couple of minutes. Work Triflex UltraCleaner into the dirt using a cleaning brush in a circular motion and rinse with water. Wipe the surface with a damp cloth.

### Canister:

General cleaning: 1 liter of Triflex UltraCleaner for 10 liters of water.

Deep cleaning: 1 liter of Triflex UltraCleaner for 5 liters of water.

Special applications: Triflex UltraCleaner can also be used undiluted. For example in the case of particularly heavy soiling such as rust or tire wear.

**Note:** Triflex UltraCleaner should not be used on glass or mirrors due to possible discolouration. Triflex UltraCleaner is not a replacement for Triflex Cleaner and should not be used for substrate pre-treatment, degreasing metals and cleaning tools.

## Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 12 months.

## Health and safety

Refer to Safety Data Sheets.

## Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.



## Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Where non-Triflex products are proposed, only solvent, alcohol and caustic free detergents or degreasants approved by Triflex should be used with Triflex systems. Consult Triflex Technical Services for further details.

Only the most recent version of this data sheet is valid.